

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product information**

Product Name : Scentinel® E Gas Odorant  
Material : 1106808, 1086435, 1086434, 1095112, 1079767, 1064505,  
1098464, 1098226, 1024677, 1024673, 1034741, 1024674,  
1024676, 1024678, 1024780, 1024782, 1024781, 1024778,  
1024783, 1036153, 1024779, 1024675, 1105014

**Company** : Chevron Phillips Chemical Company LP  
Specialty Chemicals  
10001 Six Pines Drive  
The Woodlands, TX 77380

**Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group  
E-mail address : SDS@CPChem.com  
Website : www.CPChem.com

**ODOR-FADE WARNING**

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

- Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.
- Contact with soil in underground leaks may de-odorize or remove odorant from the gas.

**Sc Sentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

- Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
- The stench of odorized gas may not awaken sleeping persons.
- Other odors may mask or hide the stench.
- Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

**SECTION 2: Hazards identification****Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

**Classification**

: Flammable liquids, Category 2  
Skin sensitization, Category 1

**Labeling**

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.  
H317: May cause an allergic skin reaction.

Precautionary Statements

: **Prevention:**  
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 Wash skin thoroughly after handling.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Carcinogenicity:****IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**ACGIH**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**SECTION 3: Composition/information on ingredients**

Synonyms : Mercaptan Mixture  
Gas Odorant

Molecular formula : Mixture

Component	CAS-No.	Weight %
t-Butyl Mercaptan	75-66-1	75 - 80
Isopropyl Mercaptan	75-33-2	13 - 18
n-Propyl Mercaptan	107-03-9	3 - 8

**SECTION 4: First aid measures**

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

If inhaled : Move to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

- Flash point : -18 °C (0 °F)  
estimated
- Autoignition temperature : 200 °C (392 °F)
- Suitable extinguishing media : Dry chemical. Carbon dioxide (CO<sub>2</sub>). Alcohol-resistant foam.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides. Sulfur oxides.

**SECTION 6: Accidental release measures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

|| For additional details, see the Exposure Scenario in the Annex portion

**SECTION 7: Handling and storage****Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

**Storage**

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
t-Butyl Mercaptan	Manufacturer	TWA	0.5 ppm,	

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

|| For additional details, see the Exposure Scenario in the Annex portion

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

- Physical state : Liquid  
 Color : Clear  
 Odor : Repulsive

**Safety data**

- Flash point : -18 °C (0 °F)  
 estimated
- Lower explosion limit : 1.4 %(V)
- Upper explosion limit : 12.5 %(V)
- Oxidizing properties : no
- Autoignition temperature : 200 °C (392 °F)
- Thermal decomposition : No data available

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

Molecular formula	: Mixture
Molecular weight	: Not applicable
pH	: Not applicable
Pour point	: No data available
Boiling point/boiling range	: 57 - 60 °C (135 - 140 °F)
Vapor pressure	: 48.00 kPa at 38 °C (100 °F)
Relative density	: 0.81 at 16 °C (61 °F)
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Relative vapor density	: 2 (Air = 1.0)
Evaporation rate	: > 1 (N-Butyl Acetate = 1)
Percent volatile	: > 99 %

**SECTION 10: Stability and reactivity**

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Possibility of hazardous reactions**

Conditions to avoid	: Not applicable.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Thermal decomposition	: No data available
Hazardous decomposition products	: Carbon oxides Sulfur oxides
Other data	: No decomposition if stored and applied as directed.

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

**SECTION 11: Toxicological information****Scentinel® E Gas Odorant****Acute oral toxicity**: Acute toxicity estimate: 10,366 mg/kg  
Method: Calculation methodAcute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method**Acute inhalation toxicity**

## t-Butyl Mercaptan

: LC50: 26643 ppm  
Exposure time: 4 h  
Species: Rat  
Sex: male and female  
Test atmosphere: vapor  
Method: OECD Test Guideline 403LC50: 22200 ppm  
Exposure time: 4 h  
Species: Rat  
Sex: male  
Test atmosphere: vapor  
Method: OECD Test Guideline 403LC50: 16500 ppm  
Exposure time: 4 h  
Species: Mouse  
Sex: male  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

## Isopropyl Mercaptan

LC50: > 32.24 mg/l  
Exposure time: 4 h  
Species: Rat  
Sex: male and female  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Test substance: yes

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

**Acute dermal toxicity**

## Isopropyl Mercaptan

: LD50: > 2,000 mg/kg  
Species: Rat**Scentinel® E Gas Odorant****Skin irritation**

: May cause skin irritation and/or dermatitis.

**Scentinel® E Gas Odorant****Eye irritation**

: May cause irreversible eye damage.

**Scentinel® E Gas Odorant****Sensitization**

: Causes sensitization.



**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

**Repeated dose toxicity**

t-Butyl Mercaptan

: Species: Rat, Male and female  
Sex: Male and female  
Application Route: Inhalation  
Dose: 9, 97, 196 ppm  
Exposure time: 13 wks  
Number of exposures: 6 hrs/d, 5 d/wk  
NOEL: > 196 ppm

Species: Rat, Male and female  
Sex: Male and female  
Application Route: oral gavage  
Dose: 10, 50, 200 mg/kg bw/day  
Exposure time: 42-53 days  
Number of exposures: Daily  
NOEL: 50 mg/kg bw/day  
Lowest observable effect level: 200 mg/kg bw/day  
Method: OECD Guideline 422

Species: Rat, Male and female  
Sex: Male and female  
Application Route: Inhalation  
Dose: 25.1, 99.6, 403.4 ppm  
Exposure time: 13 wks  
Number of exposures: 6 hrs/d, 5 d/wk  
NOEL: 99.6 ppm  
Lowest observable effect level: 403.4 ppm  
Method: OECD Guideline 413  
Target Organs: Liver, Kidney, Blood, Upper respiratory tract  
Information given is based on data obtained from similar substances.

**Reproductive toxicity**

t-Butyl Mercaptan

: Species: Rat  
Sex: male and female  
Application Route: oral gavage  
Dose: 10, 50, 200 mg/kg bw/day  
Number of exposures: Daily  
Test period: 42 -53 days  
Method: OECD Guideline 422  
NOAEL Parent: 200 mg/kg bw/day  
NOAEL F1: 50 mg/kg bw/day  
No adverse effects expected

**Developmental Toxicity**

t-Butyl Mercaptan

: Species: Mouse  
Application Route: Inhalation  
Dose: 11, 99, 195 ppm  
Exposure time: GD 6-16  
Number of exposures: 6 hrs/d  
NOAEL Teratogenicity: > = 195 ppm  
NOAEL Maternal: > = 195 ppm

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

Species: Rat  
 Application Route: Inhalation  
 Dose: 11, 99, 195 ppm  
 Exposure time: GD6-19  
 Number of exposures: 6 hrs/d  
 NOAEL Teratogenicity: > =195 ppm  
 NOAEL Maternal: > = 195 ppm

Species: Rat  
 Application Route: oral gavage  
 Dose: 10, 50, 200 mg/kg bw/day  
 Exposure time: 42-53 days  
 Number of exposures: Daily  
 NOAEL Teratogenicity: 50 mg/kg bw /day  
 NOAEL Maternal: 200 mg/kg bw /day

**Scentinel® E Gas Odorant  
Aspiration toxicity**

: May be harmful if swallowed and enters airways.  
 Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.

**CMR effects**

t-Butyl Mercaptan

: Carcinogenicity: Not available  
 Mutagenicity: Did not show mutagenic effects in animal experiments.  
 Teratogenicity: Did not show teratogenic effects in animal experiments.  
 Reproductive toxicity: No toxicity to reproduction

**Scentinel® E Gas Odorant  
Further information**

: Concentrations substantially above the TLV value may cause narcotic effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.  
 Solvents may decrease the skin.

**SECTION 12: Ecological information****Toxicity to fish**

t-Butyl Mercaptan

: LC50: 34 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 semi-static test Method: OECD Test Guideline 203

Isopropyl Mercaptan

LC50: 34 mg/l  
 Exposure time: 96 h  
 semi-static test Analytical monitoring: yes  
 Method: OECD Test Guideline 203  
 Information given is based on data obtained from similar substances.

n-Propyl Mercaptan

LC50: 1.3 mg/l  
 Exposure time: 96 h  
 Species: Pimephales promelas (fathead minnow)  
 Analytical monitoring: yes

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

Test substance: yes  
 Method: OECD Test Guideline 203  
 Toxic to aquatic organisms.

**Toxicity to daphnia and other aquatic invertebrates**

t-Butyl Mercaptan : EC50: 6.7 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202

Isopropyl Mercaptan EC50: 0.25 - 0.5 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Test substance: yes  
 Method: OECD Test Guideline 202

n-Propyl Mercaptan EC50: 0.07 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 Analytical monitoring: yes  
 Test substance: yes  
 Method: OECD Test Guideline 202  
 Very toxic to aquatic organisms.

**Toxicity to algae**

t-Butyl Mercaptan : EC50: 24 mg/l  
 Exposure time: 72 h  
 Species: Pseudokirchneriella subcapitata (green algae)  
 Method: OECD Test Guideline 201

Isopropyl Mercaptan ErC50: 21.9 mg/l  
 Exposure time: 72 h  
 Species: Pseudokirchneriella subcapitata (green algae)  
 static test Method: OECD Test Guideline 201

**M-Factor**

propane-2-thiol : M-Factor (Acute Aquat. Tox.) 1

M-Factor (Chron. Aquat. Tox.) 1

**M-Factor**

propane-1-thiol M-Factor (Acute Aquat. Tox.) 10

Elimination information (persistence and degradability)

Bioaccumulation

t-Butyl Mercaptan : Bioconcentration factor (BCF): 12  
 Bioaccumulation is unlikely.

Biodegradability : Expected to be biodegradable

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

**Ecotoxicology Assessment**

Acute aquatic toxicity	
t-Butyl Mercaptan	: Toxic to aquatic life.
Isopropyl Mercaptan	: Very toxic to aquatic life.
n-Propyl Mercaptan	: Very toxic to aquatic life.
Chronic aquatic toxicity	
t-Butyl Mercaptan	: Toxic to aquatic life with long lasting effects.
Isopropyl Mercaptan	: Very toxic to aquatic life with long lasting effects.
n-Propyl Mercaptan	: Very toxic to aquatic life with long lasting effects.
Results of PBT assessment	
t-Butyl Mercaptan	: Non-classified PBT substance, Non-classified vPvB substance
Isopropyl Mercaptan	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life., Toxic to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

|| For additional details, see the Exposure Scenario in the Annex portion

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, (-18 °C), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN)

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN)

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN)

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, ENVIRONMENTALLY HAZARDOUS

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

**SECTION 15: Regulatory information****National legislation****SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Respiratory or skin sensitization**EPCRA - EMERGENCY PLANNING COMMUNITY RIGHT - TO - KNOW**

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**US State Regulations**

Massachusetts Right To Know : n-Propyl Mercaptan - 107-03-9  
t-Butyl Mercaptan - 75-66-1  
Isopropyl Mercaptan - 75-33-2

Pennsylvania Right To Know : t-Butyl Mercaptan - 75-66-1

New Jersey Right To Know : n-Propyl Mercaptan - 107-03-9  
t-Butyl Mercaptan - 75-66-1

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

Isopropyl Mercaptan - 75-33-2


California Prop. 65 Ingredients : This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**Notification status**

Europe REACH : On the inventory, or in compliance with the inventory  
 United States of America (USA) TSCA : On the inventory, or in compliance with the inventory  
 Canada DSL : On the inventory, or in compliance with the inventory  
 Australia AICS : On the inventory, or in compliance with the inventory  
 New Zealand NZIoC : On the inventory, or in compliance with the inventory  
 Japan ENCS : On the inventory, or in compliance with the inventory  
 Korea KECI : On the inventory, or in compliance with the inventory  
 Philippines PICCS : On the inventory, or in compliance with the inventory  
 China IECSC : On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 2  
 Fire Hazard: 3  
 Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 93850

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health

**Scentinel® E Gas Odorant**

Version 2.0

Revision Date 2018-04-02

CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		