

Section 1: Product and Company Identification

Absolute Accuracy
4591 S Wayside Dr
Houston, TX 77087
(832) 571-2387

Product Code: 143

Synonyms: N/A
Recommended Use: CALIBRATION GAS
Usage Restrictions: INDUSTRIAL CALIBRATION GAS ONLY

Section 2: Hazards Identification



Danger

Hazard Classification:

Aspiration Hazard (Category 1)
Gases Under Pressure
Reproductive Toxicity (Category 2)
Specific target organ toxicity (Repeated Exposure) (Category 2)
Specific target organ toxicity (Single Exposure) (Category 3)

Hazard Statements:

Contains gas under pressure; may explode if heated
May be fatal if swallowed and enters airways
May cause damage to organs through prolonged or repeated exposure
May cause respiratory irritation;
Suspected of damaging fertility or the unborn child
Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

Do not breathe dust/fume/gas/mist/ vapors/spray..
[In case of inadequate ventilation] wear respiratory protection.
Do not handle until all safety precautions have been read and understood.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, eye protection and face protection.
Obtain special instructions before use.

Response:

Do NOT induce vomiting.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If swallowed: Rinse mouth. Do NOT induce vomiting.
Immediately call a poison center or doctor.

If exposed or concerned: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight.
Store locked up.

Disposal:

Dispose of contents and/or container in accordance with applicable regulations.

Section 3: Composition/Information on Ingredients

	CAS #	Concentration
Hexane	110-54-3	4800 PPM
Air	Not applicable	BALANCE

	Chemical Substance	Chemical Family	Trade Names
Hexane	HEXANE	Hydrocarbons, Aliphatic, Saturated	N-HEXANE; 1-HEXANE; HEXYL HYDRIDE; 1-HEXANE; NORMAL HEXANE; SKELLYSOLVE B; UN 1208; CAPROYL HYDRIDE; C6H14
Air	AIR, COMPRESSED	Inorganic gases	AIR; UN 1002 Nitrogen CAS: 7727-37-9 Oxygen CAS: 7782-44-7

Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Hexane	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Aspiration hazard. DO NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get immediate medical attention. Give artificial respiration if not breathing.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Long-term exposure to n-hexane can cause damage to the peripheral nervous system.
Air	Wash exposed skin with soap and water.	Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Get medical attention.	

Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Hexane	Regular dry chemical, carbon dioxide, water, regular foam Large fires: Use regular foam or flood with fine water spray.	Carbon monoxide, carbon dioxide and toxic and irritating fumes	<ul style="list-style-type: none"> ▪ Any appropriate escape-type, self-contained breathing apparatus. ▪ Protective material types: rubber
Air	Use extinguishing agents appropriate for surrounding fire.		<ul style="list-style-type: none"> ▪ No respirator is required under normal conditions of use.

Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Hexane	Keep unnecessary people away, isolate hazard area and deny entry.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray.
Air			Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
Hexane	Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. Remove sources of ignition.	Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).
Air		

Section 7: Handling and Storage

	Handling	Storage
Hexane	Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125F (52C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.	Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slowly. Close cylinder valve after each use; keep closed even when empty. If valve is hard to open, discontinue use and contact your supplier
Air	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.	

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Hexane	N-HEXANE: 500 ppm (1800 mg/m ³) OSHA TWA 50 ppm (180 mg/m ³) OSHA TWA (vacated by 58 FR 35338, June 30, 1993) 50 ppm ACGIH TWA (skin) 50 ppm (180 mg/m ³) NIOSH recommended TWA 10 hour(s)
Air	AIR, COMPRESSED: No occupational exposure limits established.

Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
Hexane	Wear splash resistant safety goggles with a face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any appropriate escape-type, self-contained breathing apparatus.
Air	Eye protection not required under normal conditions.	Protective clothing is not required under normal conditions.	No respirator is required under normal conditions of use.

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Hexane	Liquid	Clear	Colorless	N/A	Liquid	Faint odor, gasoline odor	N/A
Air	Gas	Clear	Colorless		Gas	Not available	

	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Hexane	-9.4 F (-23 C) (CC); -7 F (-21.7 C) (CC)	IB	139315.68 (log = 5.148) (estimated from water solubility)	437 F (225 C)	0.075	0.011
Air						

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	pH	Odor Threshold	Evaporation Rate	Viscosity
Hexane	156 F (69 C)	-139 F (-95 C)	124 mmHg @ 20 C	3 (Air=1)	0.6603	0.014% @ 20 C	Neutral	64-244 ppm	8.9 (n-butyl acetate = 1)	0.32 cP @ 25 C
Air	-317 F (-194 C)	Not available	760 mmHg @ -194 C	1	Not applicable	Slightly soluble	Not applicable	Not available	Not applicable	0.01853 cP @ 26.85 C

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
Hexane	86.18	C-H3-(C-H2)4-C-H3	Not available	Not available	Not available	675 g/l VOC (w/v)	Soluble: Alcohol, ether, chloroform, acetone, organic solvents
Air			1.29 g/L @ 0 C			Not applicable	Slightly Soluble

Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
Hexane	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Oxidizing materials, halogens, combustible materials, chlorine dioxide, fluorine, nitrogen dioxide, potassium chlorate, chlorine, chlorosulfuric acid
Air	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	None known

	Hazardous Decomposition Products	Possibility of Hazardous Reactions
Hexane	Oxides of carbon	Will not polymerize.
Air	No hazard expected.	Will not polymerize.

Section 11: Toxicology Information

Acute Effects

	Oral LD50	Dermal LD50	Inhalation
Hexane	>5 gm/kg oral-rat LD50	>2 gm/kg skin-rabbit LD50	Irritation, nausea, irregular heartbeat, headache, drowsiness, dizziness, mood swings, loss of coordination, lung congestion, nerve damage, brain damage, unconsciousness
Air	Not available	Not available	

	Eye Irritation	Skin Irritation	Sensitization
Hexane	Mild irritation	Irritation	Reproductive toxicity, Category 2; H361f: Suspected of damaging fertility. Aspiration hazard, Category 1; H304: May be fatal if swallowed and enters airways. Specific Target Organ Toxicity (repeated exposure), Category 2; H373: May cause damage to organs through prolonged or repeated exposure. Skin irritation, Category 2; H315: Causes skin irritation. Specific Target Organ Toxicity (single exposure), Category 3; H336: May cause drowsiness or dizziness. Hazardous to the aquatic environment, Chronic Category 2; H411: Toxic to aquatic life with long lasting effects.
Air	No information is available	No information is available	No significant target effects reported.

Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Hexane	Not listed.	Available.	Available.	No data
Air	Not available	Not available	No data	No data

Section 12: Ecological Information

Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Hexane	Fish toxicity: 2500 ug/L 96 hour(s) LC50 (Mortality) Fathead minnow (Pimephales promelas) Invertebrate toxicity: Not available Algal toxicity: 75 ug/L 28 hour(s) (Population Growth) Green algae (Chlamydomonas sp) Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Highly volatile from water.	Accumulates very little in the bodies of living organisms.	Not expected to leach through the soil or the sediment.
Air	Fish toxicity: Not available	Not available	Not available	Not available

Section 13: Disposal Considerations

Hexane	Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.
Air	Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

DOT Information For This Mixture

Shipping Name	Compressed gas, n.o.s. (Air, Hexane)
UN Number	UN1956
Hazard Class	2.2
Hazard Information	Non-Flammable Gas

Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
H e x a n e	Hexanes	UN1208	3	II	3	5 kg or L	N/A	N/A
A i r	Air, compressed	UN1002	2.2	Not available	2.2	Not available	Not available	Not available

Canadian Transportation of Dangerous Goods

	Shipping Name	UN Number	Class	Packing Group / Risk Group
Hexane	Hexanes	UN1208	3	II
Air	Air, compressed	UN1002	2.2	Not available

Section 15: Regulatory Information

U.S. Regulations

	CERCLA Sections	SARA 355.30	SARA 355.40
Hexane	5000 LBS RQ	Not regulated.	Not regulated.
Air	Not regulated.	Not regulated.	Not regulated.

SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
Hexane	Yes	Yes	Yes	No	No
Air	No	No	No	No	Yes

SARA 372.65

Hexane	N-HEXANE
Air	Not regulated.

OSHA Process Safety

Hexane	Not regulated.
Air	Not regulated.

State Regulations

	CA Proposition 65
Hexane	WARNING: This product can expose you to chemicals including Hexane which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .
Air	Not regulated.

Canadian Regulations

	WHMIS Classification
Hexane	B2, D2A, D2B
Air	A

National Inventory Status

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Hexane	Listed on inventory.	Not listed.	Listed on DSL.
Air	Not listed on inventory.	Not listed.	Not determined.

Section 16: Other Information

	NFPA Rating
Hexane	HEALTH=2 FIRE=3 REACTIVITY=0
Air	HEALTH=0 FIRE=0 REACTIVITY=0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard